

BFH2E - Downflow Fan Heater - Metal Bodied

The BFH2E Downflow Fan Heater is designed to provide rapid, efficient heating exactly where it is needed. Perfect for modular buildings, industrial and commercial spaces, the BFH2E combines a sleek design with advanced control features. Constructed entirely from metal, the BFH2E features a sturdy build designed to endure even the most challenging conditions, guaranteeing long-lasting durability and dependability. Compact but powerful, this metal-bodied heater is a stylish and dependable addition to both residential and commercial environments.

- Heating capacity: 1kW or 2kW (set by the user)
- Up to 2kW heat output for fast heating
- Digital variable thermostat
- 7-day programme/6 temperature settings per day
- Open window detection
- Battery backup for real-time clock
- 4 operating modes
- Copy day function
- **Safety monitoring feature:** The heater will detect and show the nature of the fault on the display screen.
- Child lock feature
- Reduces heat output to 1kW when approaching target temperature
- Automatic safety cut-out
- Can set temperatures in degrees Celsius or Fahrenheit
- Large LCD
- Fitted with 0.7m cable
- Finished in white



Dimensions (mm) & Weight (kg):

Model No.	Rating (kW)	Height	Depth	Width	Weight	Finish
BFH2E	2	170	90	330	2	White