

Screenzone Warm Air Curtains - CA1309S - CA2018S

A welcoming curtain of warmth for extra tall/wide double doorways in shops, hotels, offices and other commercial premises.

- Single/3 phase on CA1309S.
- 3 phase only on CA1312S, CA15 and CA20 models.
- Suspended or wall mounted.
- Supplied with HE8408 remote switch.
- Optional ACMC (Air Curtain Master Controller) and ACTS (Air Curtain Temperature Sensor) available.
- ACTS must be used in conjunction with ACMC.
- 2 heat settings, 2 fan speeds with remote switch.
- 8 heat settings, 8 fan speeds with optional ACMC.
- Energy efficient brushless motor.
- Multiple heaters can be controlled from one switch.
- Fan only setting for air circulation.
- Automatic safety cut-out for thermal overload protection.
- Safety monitoring feature: The feature will detect and display the nature of the fault on the display screen of ACMC controller. If ACMC controller is not used, the LED indicator light located under the heater cover will flash indicating the nature of the fault.
- Compatible with Building Management Systems.
- Finished in white.



Model No.	kW	Max Mounting Height (m)	dBA
CA1309S	9	3.4	60
CA1312S	12	3.4	60
CA1509S	9	3.4	60
CA1512S	12	3.4	60
CA1514S	14	3.4	60
CA1516S	16	3.4	60
CA2015S	15	3.4	60
CA2018S	18	3.4	60

Dimensions (mm) & Weight (kg):

Model No.	Height	Depth	Width	Weight
CA13	264	205	1305	18
CA15	264	205	1530	20
CA20	264	205	1970	25

Note: 300mm clearance from ceiling required.