

Commercial Fan Heaters - Wireless Controlled

Our commercial fan heaters provide a "heat throw" of 11m at maximum fan speed. The intelligent fan control optimises fan speed and heat output to quickly achieve and control a comfort temperature whilst maintaining a very low noise level. Provides comfort heating while working in garages, workshops and warehouses.

- 6kW, 9kW & 12kW ratings.
- Requires a separately purchased CHMC, HRXSL, CRXSL or CRXSLWIFI wireless controller.
- Single phase or 3 phase models.
- Sensor to detect the room temperature.
- Intelligent Fan Control feature: The fan automatically adjusts its speed based on the room temperature and heat output. This ensures warm airflow and prevents cold drafts.
- Incorporates EC motor for improved energy efficiency.
- Electronic fault monitoring.
- Safety monitoring feature: The heater's light will flash to indicate the nature of the fault.
- One CRXSL controller can operate multiple heaters in single zone configuration.
- One CHMC controller can operate a maximum of 8 heaters with individual control.
- Time/Manual mode in CRXSL controller:
 - Allows fan and heat settings to be adjusted manually.
 - Allows set time schedule for fan and heat settings.
- Option to select room temperature measurement on HRXSL or heaters.
- Instant directional warmth.
- 3 fan speeds, 3 heat settings with CRXSL (in Manual mode).
- 8 fan speeds, 8 heat settings with CHMC (in Manual Mode).
- Fan only setting for air circulation.



- Wall mounted with multi-directional brackets supplied (180° horizontal, 45° vertical).
- Maximum heat throw – 11 metres at full speed.
- Compatible with Building Management Systems.
- Finished in white/grey.

Commercial Heater Environmental Sensor (CHES) - Optional indoor sensor

- Compatible with CHMC controller
- Occupancy sensor
- Temperature sensor
- Remote switch connection for On/Off function or Boost



Model No.	Rating (kW)	Optimum Mounting Height (m)	Single Phase	3 Phase
CH06CSiRX	6	2 - 3.4	●	
CH06CPIRX	6	2 - 3.4		●
CH09iRX	9	2 - 3.4		●
CH12iRX	12	2 - 3.4		●

Dimensions (mm) & Weight (kg):

Height	Depth	Width	Weight	Max. dBA
272	338	332	11.5	59

CRXSL & HRXSL Energy Saving Features

- 6 temperature programmes per day
- 7-day heating programmes per week
- Maintains temperature within 0.5°C
- Set temperature in 0.5°C increments

CHMC Quick Feature Guide

- Can control up to 8 heaters as a group or individually
- Temperature sensor
- 8 fan speeds and 8 heat settings in Manual mode
- 7-day timer with 2 heating periods per day
- Wi-Fi enabled for connection to Consort Connect app - App provides full functionality of CHMC remotely