

Ceiling Fan Heaters - Wireless Controlled

Surface ceiling fan heaters are suitable for supermarket and showroom areas or where heat is required locally. They are designed to be suspended via its integral anchorage points and with a completely enclosed housing ensuring ease of installation. Recessed ceiling heaters are designed for discreet positioning in a suspended 600mm standard ceiling panel. They are ideal to heat areas where wall and floor space is at a premium such as shops and offices.

RX Ceiling Fan Heaters

- 3kW, 4.5kW or 6kW rating
- Compatible with advanced single zone controllers*
- Fan only setting for air circulation
- Wider operation range
- Quiet operation
- Sealed heater box for improved energy efficiency
- Will fit shallow 210mm recess
- LED indicator light



Surface Ceiling Fan Heater

SL Ceiling Fan Heaters

- Available in 3kW only
- Compatible with any Consort wireless controller
- Quiet operation
- Sealed heater box for improved energy efficiency
- Will fit shallow 210mm recess
- LED indicator light



Recessed Ceiling Fan Heater

*Advanced single zone controllers: CRXSL, CRXSLWIFI, HRXSL and LC controllers
Note: Wireless controllers to be purchased separately.



Safety monitoring feature for RX & SL ceiling fan heaters

The heater's light will flash to indicate the nature of the fault.

Dimensions (mm) & Weight (kg):

Model No.	Type	Rating (kW)	Depth	Width	Length	Weight	dBA	Optimum Ceiling Height (m)
HE7230RX	Recessed	3	175	595	595	7.5	46	3.0
HE7245RX	Recessed	4.5	175	595	595	7.5	47	3.3
HE7260RX	Recessed	6	175	595	595	10.5	48	3.6
HE7237RX	Surface	3	188	595	595	13.5	46	3.0
HE7247RX	Surface	4.5	188	595	595	13.5	47	3.3
HE7267RX	Surface	6	188	595	595	16.5	48	3.6

Dimensions (mm) & Weight (kg):

Model No.	Type	Rating (kW)	Depth	Width	Length	Weight	dBA	Optimum Ceiling Height (m)
HE7230SL	Recessed	3	175	595	595	7.5	46	3.0
HE7237SL	Surface	3	188	595	595	13.5	46	3.0



For full technical specifications and installation guidance, visit consortepi.com